





The economical supplement to the large document shredder: the shredded material is automatically compressed into compact bales, feeding via conveyor belt, dosage paddles pull not only smooth, but crumpled paper in the same way, rugged, wear-resistant cutting rollers made from high-grade steel for optimum cutting performance, High-power, thermally protected geared electric motor with automatic delta-wye-start, 440 mm working width; suitable for all standard computer formats, shredded material is automatically pressed into compact bales, shredder and baler operate in tandem, electronic compacting chamber level monitoring, compressing stroke is triggered automatically

⊩Protect Ensures a maximum of operation safety

Contimized interaction of the several drive parts

Convenient and fully-automatical workflow

Ensure highest user friendliness

- Manual ON/OFF control
- Auto Stop/Reverse/Restart
- Sheet steel housing with hydraulic baler



Technical data

recillical data	
Cutting size paper (mm)	5,8 mm
Amount of paper / persons:	20+ users
Security level	2
Cutting capacity (70g/m²):	120-140 sheets
Cutting capacity (80g/m²):	100-120 sheets
Cutting speed (m/sec.):	0,28 m/sec.
Working width (mm):	440 mm
DIN paper size:	A2
Motor Power kW:	8,0 kW
Supply voltage (Volt):	400 Volt
Noise level (db (A)):	68 db(A)
Weight gross (kg):	1130 kg
weight net (kg):	973 kg
Baler press force in (t)	8
Bale weight:	60-80
Bale dimensions (L/W/H) cm:	80x60x50
Warranty on machine (years):	1 years
Warranty on the fracture of cutting cylinders (years):	5 years
Width (cm):	80 cm
Depth (cm):	268 cm
Height (cm):	164 cm
In operation - depth cm:	327
Type of packaging:	2 x wooden crate
Packaging dimensions (L/W/H):	163x105x173 / 226x98x94 cm
Packing unit:	1



Accessory

- 999 69 PE bags
- 806 61 Tying tape

Optional accessory

- 864 95 Emergency stop bar
- 862 23 Extension for feed table
- 866 27 Door opening on the left side

www.intimus.com/index.php?intimus_power-14874b8e8b5c910234c1f50d3c4bac