intimus

intimus 14.87 11,8 mm / DIN 32757-1 Security level 1



The economical supplement to the large document shredder: the shredded material is automatically compressed into compact bales, feeding via conveyor belt, dosage paddles pull not only smooth, but crumpled paper in the same way, rugged, wear-resistant cutting rollers made from high-grade steel for optimum cutting performance, High-power, thermally protected geared electric motor with automatic delta-wye-start, 440 mm working width; suitable for all standard computer formats, shredded material is automatically pressed into compact bales, shredder and baler operate in tandem, electronic compacting chamber level monitoring, compressing stroke is triggered automatically

- **i-Protect** Ensures a maximum of operation safety
- Continuized interaction of the several drive parts
- Legicintrel Convenient and fully-automatical workflow
- Ensure highest user friendliness

Manual ON/OFF control

Technical data

- Auto Stop/Reverse/Restart
- Sheet steel housing with hydraulic baler

| lechnical data | |
|--|----------------------------|
| Cutting size paper (mm) | 11,8 mm |
| Amount of paper / persons: | 20+ users |
| Security level | 1 |
| Cutting capacity (70g/m²): | 200-210 sheets |
| Cutting capacity (80g/m ²): | 180-190 sheets |
| Cutting speed (m/sec.): | 0,28 m/sec. |
| Working width (mm): | 440 mm |
| DIN paper size: | A2 |
| Motor Power kW: | 8,0 kW |
| Supply voltage (Volt): | 400 Volt |
| Noise level (db (A)): | 68 db(A) |
| Weight gross (kg): | 1130 kg |
| weight net (kg): | 973 kg |
| Baler press force in (t) | 8 |
| Bale weight: | 60-80 |
| Bale dimensions (L/W/H) cm: | 80x60x50 |
| Warranty on machine (years): | 1 years |
| Warranty on the fracture of cutting cylinders (years): | 5 years |
| Width (cm): | 80 cm |
| Depth (cm): | 268 cm |
| Height (cm): | 164 cm |
| In operation - depth cm: | 327 |
| Type of packaging: | 2 x wooden crate |
| Packaging dimensions (L/W/H): | 163x105x173 / 226x98x94 cm |
| Packing unit: | 1 |
| | |



- 999 69 PE bags
- 806 61 Tying tape

Optional accessory

- 864 95 Emergency stop bar
- 862 23 Extension for feed table
- 866 27 Door opening on the left side

www.intimus.com/index.php?intimus_power-14874b8e8b5b8739d4c1f50c7c0d8a